

CABLE CONCRETE BLOCK SPECIFICATIONS

MAT	AREA	CC 20 20 lbs./s.f.		CC 35 35 lbs./s.f.		CC 45 45 lbs./s.f.		CC 70 70 lbs./s.f.		
		64 s.f.	128 s.f.	64 s.f.	128 s.f.	64 s.f.	128 s.f.	64 s.f.	128 s.f.	
	WEIGHT	1280 lbs.	2560 lbs.	2240 lbs.	4480 lbs.	2880 lbs.	5760 lbs.	4480 lbs.	8960 lbs.	
	BLOCKS/MAT	36	72	36	72	36	72	36	72	
BLOCKS	SPACING@BASE	0.5 in.		0.5 in.		0.5 in.		0.5 in.		
	SPACING@TOP	4.5 in.		4.5 in.		4.5 in.		4.5 in.		
	WEIGHT	35.6 lbs.		62.2 lbs.		80.0 lbs.		124.4 lbs.		
CABLE		LENGTH	WIDTH	LENGTH	WIDTH	LENGTH	WIDTH	LENGTH	WIDTH	
		DIAMETER	1/8 in.	1/8 in.	5/32 in.	1/8 in.	5/32 in.	1/8 in.	3/16 in.	5/32 in.
		CONSTRUCTION	1 x 19	1 x 19	1 x 19	1 x 19	1 x 19	1 x 19	1 x 19	1 x 19
		BREAKINGSTRENGTH	2100 lbs.	2100 lbs.	3300 lbs.	2100 lbs.	3300 lbs.	2100 lbs.	4700 lbs.	3300 lbs.

CABLE CONCRETE MAT DESIGN

